

High grab concrete repair bonding agent

Uses

For use with Emer-Patch concrete repair mortars including Emer-Patch Repair 40 and Emer-Patch High Build Repair.

Advantages

- Excellent bond strength between Emer-Patch repair mortars and concrete
- Improves build thickness of Emer-Patch repair mortars
- Easy to use - ready to use straight from container
- Non-flammable

Application Instructions

Preparation

All surfaces should be clean and free from dust and contamination.

Application

The substrate should be thoroughly soaked with clean water and any excess removed prior to applying one coat of Emer-Patch Primer HAR primer and scrubbing it well into the surface. **The Emer-Patch repair mortar must be applied as soon as the primer becomes tacky.** If the Emer-Patch Primer HAR is too wet, overhead and vertical build-up of the repair mortar may be difficult.

If the Emer-Patch Primer HAR primer dries before the application of the repair mortar, the area must be re-primed before proceeding. In exceptional circumstances, e.g. where a substrate/repair barrier is required or where the substrate is wet or likely to remain permanently damp, contact your local Parchem sales office for further information.

Cleaning

Wash all equipment with clean water immediately after use.

Limitations

Do not use Emer-Patch Primer HAR when the temperature is below 5°C and falling.

Estimating

Supply

Emer-Patch Primer HAR 5 litre:	FE400100-5L
--------------------------------	-------------

Coverage

Emer Patch-Primer HAR: 4 - 6 m²/litre

Storage

Emer-Patch HAR Primer should be stored in dry conditions at 5°C to 25°C in original unopened packaging. Protect from frost.

Important information

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Emer website. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.