

VOC Content Test Certificate

Tuesday 21st September 2021

Supplier: Parchem Construction Supplies Pty Ltd (1956 Dandenong Rd, Clayton, VIC, 3168, Australia)

Product Description: Emer-Seal® Paintable FC

Date Tested: September 2021 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D3960 Standard Practice for Determining Volatile Organic Compound (VOC) Content of Paints and Related Coatings Materials. ASTM D3960 test method is referred in accordance with the laboratory testing guidance from Green Building Council of Australia.

Test Data:

Specification Green Building Council of Australia Green Star Design & As Built V1.3-13.1.1B Green Star Interiors V1.3-12.1.1B	Emer-Seal [®] Paintable FC
General Purpose Adhesives and Sealants: 50 grams per Liter	12 grams per Liter as VOC content per material
	· · · · · · · · · · · · · · · · · · ·

We hereby certify that Emer-Seal® Paintable FC is below the VOC Content limits of chosen categories specified by Green Star Design, Green Building Council of Australia

Dr. Vyt Garnys PhD, BSc (Hons) AIMM, ARACI, ISIAQ ACA, AIRAH, FMA Managing Director and Principal Consultant

Tour.

Dr. Tuan Duong PhD, BEng (Chem. Eng.) Senior Consultant

à Dalah

Travis Hale BSc (Biotechnology) Senior Consultant

V2109022

Technology & Innovation

Sustainability