

(Previously known as Emer-Proof Aqua Barrier Landscape)

## High performance water based rubberised bitumen waterproofing membrane with root penetration inhibitor

### Uses

- Waterproofing of: Retaining walls  
Planter boxes  
Building foundation walls  
Below ground tanking structures
- Waterproofing/damp proof sandwich membrane
- Bond breaker for key joints and dowel bars

### Advantages

- Self priming on most common substrates (refer Priming)
- Excellent cold flexibility and elongation
- Contains root penetration inhibitor
- Low VOC
- Fast drying
- Excellent resistance to ponding water
- Non-toxic
- Solvent free and non-flammable

### Description

Emer-Proof Landscape is a high performance single component water based bituminous rubberised waterproofing membrane. Developed for the Residential & Commercial construction industry.

It is solvent free, non-flammable, and forms a highly flexible monolithic waterproofing membrane.

### Design Criteria

Emer-Proof Landscape is designed to be applied in two or more coats to produce a minimum dry film thickness of 1.0 to 1.3mm.

When required, Emer-Proof Elastic Joint Band system should be installed first in accordance with the Technical Data Sheet for the system.

The stirred Emer-Proof Landscape is laid onto the surface continually in one direction and each successive coat should be applied perpendicular to the previous coat. Allow 4 hours for film to dry between coats.

Emer-Proof Landscape should be protected from mechanical damage with "coreflute" or drainage/protection sheet.

### Coverage

Emer-Proof Landscape shall be diluted at 1:1 by weight with water as a primer on porous substrates. Apply 1 coat of primer achieving a coverage between 0.4 - 0.8L/m<sup>2</sup> depending on the porosity and condition of the substrate.

Then Emer-Proof Landscape should be applied in a 2 coat application achieving a minimum coverage of 1.5 L/m<sup>2</sup> (total) for general waterproofing applications. For heavier sealing properties, total coverage can be increased to 2 L/m<sup>2</sup> with subsequent coats. Approximate total coverage: 1.5 - 2L/m<sup>2</sup> on primed surface.

Dry film thickness: 1 - 1.3 mm

### Specification Clause

Where required, a water based bituminous rubberised liquid membrane is to be applied to offer a durable and waterproof area. The membrane shall achieve elongation >300%, tensile strength 1.47 MPa and 60% solids content. Emer-Proof Landscape meets the performance criteria and is an approved product.

### Properties

Data quoted is typical for this product, but does not constitute a specification.

<b>Solids:</b>	60%
<b>Colour:</b>	Black
<b>VOC content:</b>	8g / litre
<b>Tensile strength:</b>	1.47 MPa
<b>Shore A hardness:</b>	50 - 55
<b>Elongation:</b>	>300%

### Application Instructions

#### Surface Preparation

Surfaces must be dry, clean, sound, stable and free of loose foreign material; existing coatings; laitance; release agents; curing compounds and oil/grease residues.

#### Priming

Substrates must be primed, prior to the application of Emer-Proof Landscape.

Emer-Proof Landscape is self-priming on most porous surfaces. Dilute Emer-Proof Landscape 1:1 by weight, stir until homogeneous and then apply using a brush or a roller. Always add the water to the Landscape and do not dilute more than 1:1.

For non-porous substrates, such as metals and plastics, Emer-Proof Primer Non-Porous may be selected (see separate data sheet for further details)

#### Cracks

Cracks larger than 2mm or structural shrinkage cracks must be firstly filled with a flexible polyurethane type sealant such as Emer-Seal Paintable FC and then a 50mm wide polyethylene tape placed over the crack prior to the application of Emer-Proof Landscape. Alternatively the cracks can simply be covered with the Emer-Proof Elastic Joint Band Tape system. See Emer-Proof Elastic Joint Band system technical data sheet.

## Emer-Proof Joint Band System

The Emer-Proof Elastic Joint Band System has been developed as a superior bond breaker system to traditional sealants and bond breaker tapes.

The Emer-Proof Elastic Joint Band System includes tape (for change of direction – such as wall/wall and wall/floor joints etc.), both 270° external and 90° internal corners and an adjustable internal corner.

If being used in tanking and waterproofing applications, the Emer-Proof Landscape requires a suitable bond breaker at all substrate junctions. Use Emer-Proof Elastic Joint Band System or equivalent bond breaking methods compliant with local waterproofing standards and building recommendations.

## Mixing

Emer-Proof Landscape membrane should be lightly stirred before using.

## Membrane Application

Ensure the surface has been appropriately prepared in accordance with this product data sheet.

Emer-Proof Landscape may be applied with a roller (12 mm nap recommended), brush or standard airless sprayer (piston pump unit, 21 - 25 thou tip size) - thoroughly mix product before spraying. Its smooth texture and non-sag formulation makes it suitable for vertical and horizontal application.

The Emer-Proof Elastic Joint Band System should be installed first. Apply the mixed Emer-Proof Landscape across the substrate joins extending approximately 70mm either side of the join.

Whilst the Emer-Proof Landscape is still in a wet state install the Emer-Proof Joint Sealing Tape / corners and accessories ensuring that all air voids are expelled. Emer-Proof Elastic Joint corners should be placed in first followed by the Emer-Proof Joint Sealing Tape.

The Emer-Proof Joint Sealing Tape, corners and pipe detailing squares can be joined via a 50mm overlap, sandwiching a small amount Emer-Proof Landscape liquid membrane between the overlapping faces. Each successive coat should be applied at 90 degrees to the previous coat.

Emer-Proof Landscape is laid onto the surface continually in one direction; it should not be brushed out. Brooms, brushes etc. should be regularly washed during the operation and at any breaks as follows: Keep available a container filled with sufficient strong detergent / water solution to fully cover the broom or brush. Soak the brush in the solution and shake out before use. As work progresses, rinse the brush at frequent intervals to prevent it clogging, and again shake out before resuming. During any breaks in work the brushes should be left to soak in this solution.

Allowing a drying time of 4 hours between coats.

Conduct a final inspection on the surface of the membrane prior to commencing back-filling to ensure no pinholes exist.

A further coat may be required if imperfections or pinholes are present in the membrane.

## Recoating

Emer-Proof Landscape may be recoated 4 hours after previous coat has been allowed to dry.

Shorter times may be acceptable in good drying times.

## Key joints and dowel bars

Emer-Proof Landscape is suitable as a coating on key joints and dowel bars. Provided the Emer-Proof Landscape is allowed to dry prior to pouring the next section of concrete, it forms an effective slip layer and so allows relative movement between sections.

## Drying Times

	23°C, 50% RH	10°C, 50% RH
Recoat time:	4 hours	8 hours
Dry film:	24 hours	48 hours
Backfilling:	3 days	4 days

## Protection

Where the membrane is to be back filled, such as with basement applications, Emer-Proof Landscape should be protected from mechanical damage with “coreflute” or suitable drainage/protection system.

## Cleaning

Splashes of Emer-Proof Landscape on paintwork etc. should be wiped off immediately using a cloth dampened with water and a strong detergent solution. Brushes and brooms etc. should be soaked in a strong detergent solution immediately after application has finished. Hands and skin may be cleaned using a proprietary waterless hand cleaner, but prevention of soiling is better practice by wearing gloves and overalls.

Where Emer-Proof Landscape has been allowed to dry on equipment or surfaces it may be removed using either Solvent 10 or mechanical means.

## Maintenance

No special requirements, any damage identified during normal inspections should be repaired or replaced as appropriate.

## Limitations

Emer-Proof Landscape is not recommended for continuous water immersion or as a membrane on internal walls subject to back pressure.

Emer-Proof Landscape has not been designed as an exposed wearing course membrane. Emer-Proof Landscape must be covered and cannot be exposed to UV on a permanent basis. Not designed to be finished directly over with tiles, screeds, renders or paints.

# Emer-Proof® Landscape

---

## Please Note:

Application of all liquid applied membranes and primers should always refer to the surface temperature conditions before commencing and not just ambient temperatures. (There are limitations to how hot/cold the surface temperature can be, when applying liquid based membrane or primer).

For example: ambient temperatures may be 10°C but the substrate could be 0°C and have frost issues. The same applies with higher temperatures: ambient temperature may be 26°C but have a substrate temperature of 36°C.

## Supply

<b>Emer-Proof Landscape – 15L Pail</b> Coverage: 1.5 to 2.0 litre / m <sup>2</sup> (2 coats total)	FC000988-15L
<b>Emer-Proof Primer Non-Porous – 4L Pail</b> Coverage: 1L/10m <sup>2</sup>	FC043123-4L
<b>Emer-Proof Elastic Joint Band Tape</b> 120mm wide x 10m Roll	FC000691-UNIT
<b>Emer-Proof Elastic Joint Band Corner</b> Internal 90° 135mm x 135mm	FC043270-UNIT
<b>Emer-Proof Elastic Joint Band Corner</b> External 270° 135mm x 135mm	FC043275-UNIT
<b>Emer-Proof Elastic Joint Band Corner</b> Adjustable Internal – 135mm x 135mm	FC043125-UNIT

## Storage

Emer-Proof Landscape should be kept in a dry store in the original, unopened containers at temperatures between 5°C and 30°C. Do not use if there are lumps in the product or the product has a bacterial smell. If stored in high temperature and high humidity locations the shelf life may be reduced.

## Important notice

A Safety Data Sheet (SDS) and Technical Data Sheet (TDS) are available from the Emer website. Read the SDS and TDS carefully prior to use as application or performance data may change from time to time. In emergency, contact any Poisons Information Centre (phone 13 11 26 within Australia) or a doctor for advice.

## Product disclaimer

This Technical Data Sheet (TDS) summarises our best knowledge of the product, including how to use and apply the product based on the information available at the time. You should read this TDS carefully and consider the information in the context of how the product will be used, including in conjunction with any other product and the type of surfaces to, and the manner in which, the product will be applied. Our responsibility for products sold is subject to our standard terms and conditions of sale. Parchem does not accept any liability either directly or indirectly for any losses suffered in connection with the use or application of the product whether or not in accordance with any advice, specification, recommendation or information given by it.



Emer-Proof® is a registered trade mark of Parchem Construction Supplies Pty Ltd

**Parchem Construction Supplies Pty Ltd**  
1956 Dandenong Rd Clayton VIC 3168  
Phone: 1300 283 668  
www.emer.com.au  
ABN 80 069 961 968